

# Vertical balers

## B-series B3



### WHERE SPACE IS LIMITED

The B3 is one of the smallest balers in our machine programme. With a very small base area and a 230V connection, it is easy to locate.

To ensure the chamber is not overloaded, the B3 is equipped with a full-indicator which twinkles when the baler is full, and the press plate stays down.

Furthermore the baling process is simplified as the straps can be pulled directly through the main door.



#### Technical specifications

|                            |                  |
|----------------------------|------------------|
| Press force (t)            | 3                |
| Power supply               | 1x230V 50Hz 10A  |
| Motor (kW)                 | 1.1              |
| Noise level (dB)           | 65-68            |
| Cycle time (sec)           | 18               |
| Dimensions LxWxH (mm)      | 845 x 745 x 1965 |
| Weight (kg)                | 310              |
| Filling opening WxH (mm)   | 700 x 460        |
| Filling height (mm)        | 755              |
| Chamber height (mm)        | 1100             |
| Stroke (mm)                | 550              |
| Bale size WxDxH (mm)       | 700 x 500 x 650  |
| Bale weight cardboard (kg) | 30-50            |
| Bale weight plastic (kg)   | 40-60            |



**1** Compact your waste and eject the finished bale. **2** Remove and store the bale until collection. **3** The baler has a simple control panel and is equipped with easily understood pictograms. **4** The strap rolls are easy to replace in front of the machine.

- **Simple and safe operation**  
Green light twinkles when chamber is full.
- **Easy to replace strap rolls**  
They are placed in front
- **Compact design**  
With low overall height